



عنوان الإضاءة
LIGHTING ADDRESS

ELECTRICAL ACCESSORIES AND CONNECTORS



CODE PRODUCT	CODE PRODUCT
IP CODE	IP20
ELECTRICAL PARAMETER	450V/24A
STRIPPING LENGTH	8-10MM
APPLICABLE CONDUCTOR	0.75-2.5MM ² (SINGLE HARD CONDUCTOR) 0.75-2.5MM ² (MULTI-STRAND FLEXIBLE CONDUCTOR)
SPECIFICATION SIZE	19.8 X 25.5 X 17.9MM
/	/



CODE PRODUCT	11011461
IP CODE	IP20
ELECTRICAL PARAMETER	250V/4KV/32A
STRIPPING LENGTH	9-10MM
APPLICABLE CONDUCTOR	0.08-2.5MM ² (SINGLE HARD CONDUCTOR) 0.08-4.0MM ² (MULTI-STRAND FLEXIBLE CONDUCTOR)
SPECIFICATION SIZE	20.5 X 12.4 X 14.5MM
/	/



CODE PRODUCT	11011462
IP CODE	IP20
ELECTRICAL PARAMETER	250V/4KV/32A
STRIPPING LENGTH	12MM
APPLICABLE CONDUCTOR	0.08-2.5MM ² (SINGLE HARD CONDUCTOR) 0.08-4.0MM ² (MULTI-STRAND FLEXIBLE CONDUCTOR)
SPECIFICATION SIZE	39.6 X 13.7 X 14.5MM
/	/



CODE PRODUCT	11011463
IP CODE	IP20
ELECTRICAL PARAMETER	250V/4KV/32A
STRIPPING LENGTH	12MM
APPLICABLE CONDUCTOR	0.08-2.5MM ² (SINGLE HARD CONDUCTOR) 0.08-4.0MM ² (MULTI-STRAND FLEXIBLE CONDUCTOR)
SPECIFICATION SIZE	39.6 X 13.7 X 22MM
/	/





CODE PRODUCT	11011464
IP CODE	IP20
ELECTRICAL PARAMETER	250V/4KV/32A
STRIPPING LENGTH	8-12MM
APPLICABLE CONDUCTOR	0.08-2.5MM ² (SINGLE HARD CONDUCTOR) 0.08-4.0MM ² (MULTI-STRAND FLEXIBLE CONDUCTOR)
SPECIFICATION SIZE	39.6 X 13.7 X 30.5MM
/	/






CODE PRODUCT	11011465
IP CODE	IP20
ELECTRICAL PARAMETER	250V/4KV/32A
STRIPPING LENGTH	8-12MM
APPLICABLE CONDUCTOR	0.08-2.5MM ² (SINGLE HARD CONDUCTOR) 0.08-4.0MM ² (MULTI-STRAND FLEXIBLE CONDUCTOR)
SPECIFICATION SIZE	39.6 X 13.7 X 38MM
/	/






CODE PRODUCT	11011458
IP CODE	IP68
RATED POWER	IEC/NSW:17.5A 450VAC ETL:10A 300VAC
NUMBER OF POLES	2P
RATED CONNECTING CAPACITY	European/Australia: 0.5-1.5mm ² American: SJOW 18AWG
TEMPERATURE RANGE	-40°C~+105°C
AVAILABLE CABLE DIAMETER	2*M16(4-8mm) Round rubber cable



CODE PRODUCT	/
IP CODE	IP68
RATED POWER	IEC/NSW:17.5A 450VAC ETL:10A 300VAC
NUMBER OF POLES	2P/3P
RATED CONNECTING CAPACITY	European/Australia: 0.5-1.5mm ² American: SJOW 18AWG
TEMPERATURE RANGE	-40°C TO +105°C
AVAILABLE CABLE DIAMETER	2*M16(3-6.5mm/5-9mm) Round rubber cable



CODE PRODUCT	11011456
IP CODE	IP68
RATED POWER	IEC/NSW:17.5A 450VAC ETL:10A 300VAC
NUMBER OF POLES	2P/3P
RATED CONNECTING CAPACITY	European/Australia: 0.5-1.5mm ²
TEMPERATURE RANGE	-40°C TO +105°C
AVAILABLE CABLE DIAMETER	2*M18(5-10MM) Round rubber cable





CODE PRODUCT	11011460
IP CODE	IP68
RATED POWER	≤16A - 400VAC
NUMBER OF POLES	2P/3P
RATED CONNECTING CAPACITY	0.5-2mm
TEMPERATURE RANGE	-40°C TO +105°C
AVAILABLE CABLE DIAMETER	8-12mm (normal), 6-10mm



PLUG APERTURE




NUMBER OF POLES





CODE PRODUCT	11011459
IP CODE	IP68
RATED POWER	IEC/NSW:24A 450VAC ETL:10A 300VAC
NUMBER OF POLES	2P/3P
RATED CONNECTING CAPACITY	European/Australia: 0.5-2.5mm ² American: SJOW 14-18AWG
TEMPERATURE RANGE	-40°C TO +105°C
AVAILABLE CABLE DIAMETER	3*M20 (4-8mm/6-11mm) Round rubber cable



PLUG APERTURE




NUMBER OF POLES





CODE PRODUCT	1101126
IP CODE	IP68
RATED POWER	IEC/NSW:32A 450VAC ETL:18A 300VAC
NUMBER OF POLES	2P/3P/4P/5P
RATED CONNECTING CAPACITY	European/Australia: 0.5-4.0mm ² American: SJOW 12-14AWG
TEMPERATURE RANGE	-40°C TO +105°C
AVAILABLE CABLE DIAMETER	3*M25 (4-8mm/8-12mm/10-14mm) Round rubber cable






PLUG APERTURE





NUMBER OF POLES



CODE PRODUCT	1101125
IP CODE	IP68
RATED POWER	IEC/NSW:32A 450VAC ETL:18A 300VAC
NUMBER OF POLES	2P/3P/4P/5P
RATED CONNECTING CAPACITY	European/Australia: 0.5-4.0mm ² American:SJOW 12-14AWG
TEMPERATURE RANGE	-40°C--+105°C
AVAILABLE CABLE DIAMETER	1" M25 - 1 in: 4-8mm/8-12mm/10-14mm 3 out/4 out: 3-7mm



CODE PRODUCT	11011454
IP CODE	IP68
RATED POWER	IEC/NSW:24A 450VAC ETL:10-15A 300VAC
NUMBER OF POLES	2P
RATED CONNECTING CAPACITY	EUROPEAN/AUSTRALIA: 0.5-2.5MM ² AMERICAN:SJOW 14-18AWG
TEMPERATURE RANGE	-40°C--+105°C
AVAILABLE CABLE DIAMETER	2" M20(4-8mm/6-11mm) Round rubber cable



CODE PRODUCT	11011455
IP CODE	IP68
RATED POWER	IEC/NSW:24A 450VAC ETL:10-15A 300VAC
NUMBER OF POLES	2P/3P
RATED CONNECTING CAPACITY	European/Australia: 0.5-2.5mm ² American:SJOW 14-18AWG
TEMPERATURE RANGE	-40°C TO +105°C
AVAILABLE CABLE DIAMETER	4" M20(4-8mm/6-11mm) Round rubber cable

